

JCPT(HD)

Self-Propelled Scissor Lifts (Hydraulic Motor Drive)



Dingli



	JCPT0808HD	JCPT1008HD	JCPT1012HD	JCPT1212HD
S.W.L	380kg	230kg	450kg	320kg
S.W.L On Extension	113kg	113kg	113kg	113kg
Max. Occupants	2	2	2	2
A Working Height	8.00m	10.00m	10.00m	12.00m
B Platform Floor Height	6.00m	8.00m	8.00m	10.00m
C Overall Length	2.48m	2.48m	2.48m	2.48m
D Overall Width	0.81m	0.81m	1.15m	1.15m
Overall Height _(Rails Up)	2.20m	2.32m	2.32m	2.45m
E Overall Height _(Rails Down)	1.87m	1.99m	1.78m	1.91m
F Platform Size _(Length/Width)	2.27m×0.81m	2.27m×0.81m	2.27m×1.12m	2.27m×1.12m
G Platform Extension Size	0.90m	0.90m	0.90m	0.90m
Ground Clearance _(Stowed/Raised)	0.10m/0.019m	0.10m/0.019m	0.10m/0.019m	0.10m/0.019m
Wheelbase	1.87m	1.87m	1.87m	1.87m
Turning Radius _(Inside/Outside)	0m/2.10m	0m/2.10m	0m/2.20m	0m/2.20m
Drive/Lifting Motor	24V/3.3kW	24V/3.3kW	24V/3.3kW	24V/4.5kW
Travel Speed _(Stowed)	3.5km/h	3.5km/h	3.5km/h	3.5km/h
Travel Speed _(Raised)	0.8km/h	0.8km/h	0.8km/h	0.8km/h
Up/Down Speed	24/54sec	28/40sec	28/38sec	45/36sec
Batteries	4×6V/225Ah	4×6V/225Ah	4×6V/225Ah	4×6V/240Ah
Integrated Charger	24V/25A	24V/25A	24V/25A	24V/25A
Gradeability	25%	25%	25%	25%
Maximum Working Slope _(CE)	1.5°/3°	1.5°/3°	1.5°/3°	1.5°/3°
Maximum Working Slope _(ANSI)	2°/3°	2°/3°	2°/3°	2°/3°
Tyres	Φ381×127mm	Φ381×127mm	Φ381×127mm	Φ381×127mm
Weight _(CE)	2085kg	2140kg	2615kg	2945kg
Weight _(ANSI)	1985kg	2140kg	2215kg	2510kg

Standard Equipment

- Proportional Controls
- Self-lock Gate On Platform
- Automatic Pothole Protection
- Drivable At Full Height
- Onboard Diagnostic System
- Non Marking Tyre
- Automatic Brake System
- Emergency Lowering System
- Emergency Stop Button
- Cylinder Holding Valve
- Extended Platform
- Horn
- Forklift Pockets
- Charger Protection
- All Motion Alarm
- 2WD
- Safety Brackets
- Hour Meter
- Flashing Beacon
- Tilt Sensor With Alarm
- Folding Guardrails

Options

- Overload Sensor With Alarm
- AC Power To Platform
- Platform Work Lights
- Airline To Platform



Folding Guardrails



Compact Turning Radius



Swing Out Tray



Gradeability



Extended Platform



Flashing Beacon



Emergency Lowering System



Safety Bracket